

Table with 3 columns: Supplier's name or trade mark, Value, Unit. Rows include: Model identifier (E100EXI-193-002), Annual Energy Consumption - AEEchood (45.9 kWh/a), Energy Efficiency Class (A), Fluid Dynamic Efficiency - FDEhood (29.8 %), Light Efficiency - LEhood (76.1 lux/W), Grease Filtering Efficiency - GFEhood (65.1 %), Minimum Air Flow in normal use (280 m³/h), Maximum Air Flow in normal use (540 m³/h), Air Flow at intensive/boost setting (620 m³/h), A-weighted Sound Power Emission at minimum speed (52 dB(A) re 1pW), A-weighted Sound Power Emission at maximum speed (67 dB(A) re 1pW), A-weighted Sound Power Emission at intensive or boost speed (70 dB(A) re 1pW), Power consumption off mode - Po (NA W), Power consumption in standby mode - Ps (0.49 W).

Additional Product Information compliant to commission regulation (EU) No 66/2014 and UK SI 2019 No. 539

Table with 3 columns: Symbol, Value, Unit. Rows include: Time increase factor (f, 0.9), Energy Efficiency Index (EEIhood, 53.7), Measured air flow rate at best efficiency point (QBEP, 300 m³/h), Measured air pressure at best efficiency point (PBEP, 420 Pa), Maximum air flow (Qmax, NA m³/h), Measured electric power input at best efficiency point (WBEP, 117.5 W), Nominal power of the lighting system (WL, 10 W), Average illumination of the lighting system on the cooking surface (Emiddle, 761 lux).

